

PRODUCT COMPARISON

	HOME SERIES	PRO SERIES	DUAL Master Version	DUAL Slave Version
CHARGING STATIONS	Up to 22 kW	Up to 22 kW	Up to 2x 22 kW	Up to 2x 22 kW
1 phase 240 V connection	✓	✓	⊗	⊗
3 phases 400 V connection	✓	✓	✓	✓
Adjustable current	✓	✓	✓	✓
Socket with lock - type 2 version	✓	✓	✓	✓
Fixed cable - Type 2 version	✓	✓	⊗	⊗
Leakage current protection 6mA DC	✓	✓	✓	✓
Internal Residual current device	⊗	⊗	✓	✓
Overcurrent and short-circuit protection	⊗	⊗	✓	✓
OCPP communication	✓	✓	✓	✓
MID metering	✓	✓	✓	✓
Lan data connection	✓	✓	✓	✓
Wifi data connection	✓	Optional	Optional	Optional
4G SIM data connection	Optional	Optional	✓	Optional
DLB - Dynamic load balancing	Optional	Optional	Optional	Optional
DLM - Dynamic load management	⊗	✓	✓	✓
Master/Slave mode	⊗	✓	✓	✓
Communication with P1 meter	Optional	Optional	Optional	Optional
ISO 15118 ready	⊗	✓	✓	✓
Rfid reader	✓	✓	✓	✓
Display	✓	✓	✓	✓
Status Leds	✓	✓	✓	✓
QR code (online payment/Help)	✓	✓	✓	✓

All SNIGG charging devices come with a legal guarantee of two years from the date of purchase.