

# PRODUCT COMPARISON

	HOME SERIES	BUSINESS SERIES	DUAL Master Version	DUAL Slave Version
<b>CHARGING STATIONS</b>	Up to 22 kW	Up to 22 kW	Up to 2x 22 kW	Up to 2x 22 kW
1 phase 240 V connection	✓	✓	⊗	⊗
3 phases 400 V connection	✓	✓	✓	✓
Adjustable current	✓	✓	✓	✓
Socket with lock - type 2 version	✓	✓	✓	✓
Fixed cable - Type 2 version	✓	✓	⊗	⊗
Leakage current protection 6mA DC	✓	✓	✓	✓
Internal Residual current device	⊗	⊗	✓	✓
Internal overcurrent and short-circuit protection	⊗	⊗	✓	✓
OCPP communication	✓	✓	✓	✓
MID metering	✓	✓	✓	✓
Lan data connection	✓	✓	✓	✓
Wifi data connection	✓	Optional	Optional	Optional
<b>4G SIM data connection</b>	⊗	Optional	✓	Optional
DLB - Dynamic load balancing	✓	✓	✓	✓
<b>DLM - Dynamic load management</b>	⊗	✓	✓	✓
<b>Master/Slave mode</b>	⊗	✓	✓	✓
Communication with P1 meter	✓	✓	✓	✓
<b>ISO 15118 (Plug&amp;Charge, V2G Ready, AutoCharge)</b>	⊗	✓	✓	✓
<b>Compatible with Home Energy Management Systems</b>	⊗	✓	✓	✓
Rfid reader	✓	✓	✓	✓
Display	✓	✓	✓	✓
Status Leds	✓	✓	✓	✓
QR code (online payment/Help)	✓	✓	✓	✓

All SNIGG charging devices come with a legal guarantee of two years from the date of purchase.